

PART NUMBER:

TYPE: JOB NAME:



ORDERING INFORMATION

1 MODEL* & SIZE

- VODA 23** 23" Diameter
- VODA 34** 34" Diameter

2 COLOR TEMP.

- 3000** 3000K
- 3500** 3500K
- 4000** 4000K

3 CRI

- 80** (standard)
- 90**

4 WATTAGE

- 23** 23 Watts
- 53** 53 Watts

5 VOLTAGE

- UNV** 120-277V (0-10V Dimming)

6 MOUNTING OPTIONS

- CPC/DM/08** 8" Canopy with Driver, cable mounted
- CPC/DM/06** 6" Canopy with Remote Driver, cable mounted

7 INSIDE COLOR CODE

- BKG** Gloss Black
- BKS** Satin Black
- BRZ** Bronze
- WHG** Gloss White
- WHS** Satin White
- BLU** Blue
- GRN** Green
- GDS** Satin Gold
- CRD** Cardinal Red
- SLV** Silver
- RAL** RAL_____
- CUS** CUSTOM

SPECIFICATIONS

SIZES:	22.5" or 34" diameters.
CONSTRUCTION:	Rigid ring body construction to allow heat dissipation and prevent damaging and warping. Construction of the 24" rings to 60" rings are fabricated as non-modular single frame rings.
DIFFUSERS:	Precision cut acrylic lens eliminates any LED pixelation and provides smooth symmetric distribution.
MOUNTING CONFIGURATIONS:	Standard configuration is provided with 3 griplock cables and cord that mount to canopy.
SUPPORTS:	All fixtures supplied standard with 8 feet stainless steel cables. Additional cable lengths available on request.
DRIVERS:	LED drivers are 120-277V and 0-10V dimming. Drivers are directed mounted in the canopy or optional remote mounted (RM) driver in enclosure.
LED:	LED's are mounted to metal surface to maximize heat dissipation. Available in 3000, 3500 or 4000K. Standard 80CRI, 90CRI optional.
ILLUMINATION:	L22.5" delivers 2154 lumens at 23 watts. 34" delivers 4965 lumens at 53 watts.
FINISHES:	Powder coated finish applied to housing and canopies. Available in a variety of powder coated finishes.
FABRICATION:	Fabricated and assembled in the US.
LISTINGS:	UL listed for dry or damp indoor locations.
WARRANTY:	5 year limited warranty on LED and electronic parts. Consult terms and conditions for full details.

RENDERINGS AND DIMENSIONS

