

Illusions Dome

PART NUMBER:	
TYPE:	JOB NAME:



ORDERING INFORMATION	
2 COLOR TEMP. 3000 3000K 3500 3500K 4000 4000K	
4 WATTAGE 20 20 Watts 22 22 Watts 24 24 Watts	
5 VOLTAGEUNV 120-277V (0-10V Dimming)6 MOUNTING OPTIONS	
☐ CPC/DM/08 8" Canopy with Driver, Cable mounted ☐ STM/DM/08 8" Canopy with Driver, Stem mounted	



Illusions Dome

SPECIFICATIONS

14" Globe with 22.5" Dome cover SIZES:

18" Globe with 34" Dome cover

CONSTRUCTION: Acrylic sphere and spun reflector mounted to rigid

> metal cover and suspended to Canopy. LED driver is mounted in canopy or can be remote mounted in enclosure. Cover, stem and canopy finished in durable

powder coated finish.

Precision cut acrylic lens eliminates any LED pixelation and **DIFFUSERS:**

provides smooth symmetric distribution.

Standard configuration is provided with (3)12" sections **MOUNTING CONFIGURATIONS:**

and (1) 8" section. For longer lengths or dedicated stem lengths, please consult factory. Can also be provided

with cables for suspended mounting

DRIVERS: LED drivers are 120-277V and 0-10V dimming. Drivers are

direct mounted in the canopy or optional remote

mounted (RM) driver in enclosure.

LED's are mounted to metal surface to maximize heat LED:

dissipation. Available in 3000, 3500 or 4000K.

Standard 80CRI, 90CRI optional.

14-16" globe: 2,318 lumens at 20W **ILLUMINATION:**

> 18-20" globe: 2,687 lumens at 22W 22" globe: 2,821 lumens at 23W

For other outputs and configurations, please consult factory

FINISHES: Powder coated finish applied to housing and canopies.

Available in a variety of powder coated finishes.

Fabricated and assembled in the US. **FABRICATION:**

UL listed for dry or damp indoor locations. LISTINGS:

5 year limited warranty on LED and electronic parts. **WARRANTY:**

Consult terms and conditions for full details.

RENDERINGS AND DIMENSIONS

