



SPECIFICATIONS

SIZES:	24"-144" Custom sizes available	LED:	LED's are mounted to vertical surfaces to maximize heat dissipation. Available 2700K-5000K. Standard 80 CRI, 90 CRI optional.
FRAME SIZE:	2"W x 2.75"H	ILLUMINATION:	Available designed lumens or 450 or 900 lumens/linear ft.
CONSTRUCTION:	Rigid outer body construction to allow heat dissipation and prevent damaging and warping. Construction of the 24" rings to 60" rings are fabricated as non-modular single frame rings. 72" and larger designs are fabricated in modular sections to be assembled on location.	FINISHES:	Powder coated finish applied to housing and canopies. Available in a variety of powder coated finishes.
DISTRIBUTIONS:	Direct or Direct/Indirect options available	FABRICATION:	Fabricated and assembled in the US
DIFFUSERS:	Precision cut acrylic lens eliminates any LED pixelation and provides smooth symmetric distribution.	LISTINGS:	UL listed for indoor applications
MOUNTING CONFIGURATIONS:	Cables can be centered pitched to the canopy (CPC) or Vertical Suspended (VS). Check specifications for sizes and options. Cables can be adjusted to desired height.	WARRANTY:	5 year limited warranty on LED and electronic parts. Consult terms and conditions for full details.
SUPPORTS:	All fixtures supplied standard with 8 feet stainless steel cables. Additional cable lengths available on request. <i>Adequate ceiling support required at aircraft cable mounting points. Request installation guide specific to the size and illumination for each fixture upon ordering to identify mounting support points.</i>		
DRIVERS:	LED drivers are 120-277V and 0-10V dimming. Drivers can be directed mounted (DM) in the canopy (DM) or remote mounted (RM) above the ceiling. Larger rings may require additional drivers.		

PART NUMBER:

TYPE: JOB NAME:

ORDERING INFORMATION

1 MODEL* & SIZE

- ECLIPSE 24** 24" Diameter
- ECLIPSE 36** 36" Diameter
- ECLIPSE 48** 48" Diameter
- ECLIPSE 60** 60" Diameter
- ECLIPSE 72** 72" Diameter
- ECLIPSE 84** 84" Diameter
- ECLIPSE 96** 96" Diameter
- ECLIPSE 120** 120" Diameter
- ECLIPSE 144** 144" Diameter
- ECLIPSE 168** 168" Diameter

2 COLOR TEMP.

- 2700** 2700K
- 3000** 3000K
- 3500** 3500K
- 4000** 4000K

3 CRI

- 80** 80 CRI (Standard)
- 90** 90 CRI

4 DIRECT/INDIRECT

- D** Downward Distribution
- D/IND** Direct/Indirect Distribution

5 LM/FT

- 450** 450 Designed Lumens/ft
- 900** 900 Designed Lumens/ft

6 VOLTAGE

- UNV** 120-277V (0-10V Dimming)

7 MOUNTING

- CPC/DM/09** 9" Canopy with Driver in Canopy, Cable Pitched from Canopy
- CPC/DM/12** 12" Canopy with Driver in Canopy, Cable Pitched from Canopy
- CPC/RM/08** 8" Canopy with Remote Driver, Cable Pitched from Canopy
- CPC/RM/12** 12" Canopy with Remote Driver, Cable Pitched from Canopy
- VS/DM/09** 9" Canopy with Driver in Canopy, Vertical Suspension
- VS/DM/12** 12" Canopy with Driver in Canopy, Vertical Suspension
- VS/RM/08** 8" Canopy with Remote Driver, Vertical Suspension
- VS/RM/12** 12" Canopy with Remote Driver, Vertical Suspension

8 COLOR CODE

- CRD** Cardinal Red
- BKG** Gloss Black
- BKS** Satin Black
- BLU** Blue
- GRN** Green
- YLW** Yellow
- ANA** Anodized Aluminum
- ORG** Orange
- BRZ** Bronze
- WHS** Satin White
- WHG** Gloss White
- BNK** Brushed Nickel

* S denotes singular construction and M for modular.