

EU1002

Drum with Ring Pendant

EUGLOW Collection



TY	PE:		J	OB NAM	E:		
OKDEKI	ING IIVI	ORMAT	ION				
1 MODEL	* & SIZE		2	COLO	OR T	ЕМР.	
EU1016-3				3000 3 3500 3 4000 4	3500	К	
3 CRI 80 80 CRI (Standard			4	34 67	34W		
MOUN CPC/DM/ STM-CPC canopy CPC/RM/	UNV 120-277V (0-10V Dimming) MOUNTING OPTIONS CPC/DM/08 8" Canopy with Driver, Cable mounted to center canopy STM-CPC/DM/08 8" Canopy with Driver, Stem and Cable mounted to center						
7 INSIDE	ACRYLIC	8 OUTSIE	DE ACR	RYLIC	7	PAINT	FINISH
BLUE GREEN Orange MAROON YELLOW PURPLE SANDY BLACK GOLD TEAL	Yellow	WA BLUE GREEN Orange MAROON YELLOW PURPLE SANDY BLACK GOLD TEAL	Yellow			WHS BLU GRN GDS CRD SLV RAL	Satin Black Bronze Gloss White Satin White Blue Green Satin Gold Cardinal Red Silver RAL
						CUSTO	M Custom color

PART NUMBER:



EU1002

Drum with Ring Pendant

SPECIFICATIONS

SIZES: 22"W x 8"H

26"W x 8"H 32"W x 8"H 38"W x 8"H

Acrylic drum shade mounted to rigid metal cover and **CONSTRUCTION:**

suspended to Canopy. LED driver is mounted in canopy or can be remote mounted in enclosure. Covers, stem and canopy finished in durable powder coated finish.

Precision formed acrylic drums eliminates any LED **DIFFUSERS:**

> pixelation and provides smooth symmetric distribution. Optional perimeter acrylic colors are available. Please

consult factory for additional color options.

MOUNTING

Available configurations are provided with (4) griplock cables and can be specified to mount to the Center **CONFIGURATIONS:** Canopy or vertical suspension to the ceiling. 60" sizes

requires center stem and (4) griplock cables. This option

can also be used for smaller sizes.

LED drivers are 120-277V and 0-10V dimming. Drivers are **DRIVERS:**

direct mounted in the canopy or optional remote

mounted (RM) driver in enclosure.

LED's are mounted to metal surface to maximize heat LED:

dissipation. Available in 3000, 3500 or 4000K.

Standard 80CRI, 90CRI optional.

22" Drum: 1656 lumens at 24W **ILLUMINATION:**

> 26" Drum: 2,483 lumens at 36W 32" Drum: 4,965 lumens at 56W 38" Drum: 4.965 lumens at 56W

For other outputs and configurations, please consult factory

Powder coated finish applied to housing and canopies. **FINISHES:**

Available in a variety of powder coated finishes.


Fabricated and assembled in the US. **FABRICATION:**

UL listed for dry or damp indoor locations. LISTINGS:

5 year limited warranty on LED and electronic parts. **WARRANTY:**

Consult terms and conditions for full details.

RENDERINGS AND DIMENSIONS



CONFIGURATION TABLE						
CONFIGURED SIZE	XX DIMENSION	YY DIMENSION				
20	Ø 20.25"	Ø 22.125"				
24	Ø 24.25"	Ø 26.125"				
30	Ø 30.25"	Ø 32.125"				
36	Ø 36.25"	Ø 38.125"				



ACRYLIC COLOR OPTIONS



METAL COLOR OPTIONS

